

IS291-USB2.0

2MP USB2.0 Camera Module



SPECIFICATION

Image Sensor	1/2.8" CMOS IMX291
Pixel Size	2.9um(H) x 2.9um(V)
Resolution	2.0 Megapixel 1920H x 1080V
Output Format	MJPEG, YUV2
FOV	80 degree, more view angle for option by requirement
Lens	EFL: 4.2MM F/NO: 2.4MM
Focus type	Fixed focus
Shutter type	Electronic Rolling shutter
Audio Input	No
Protocol & Connection	Plug & Play, UVC compliant
Output & Power Supply	USB2.0
Power Socket	4P 2.0mm socket
Supported OS	Win XP/Vista/Win7/Win8/Win10 MAC OS X El Capitan 10.11.4, Linux /Android, Wince with UVC

Controllable Features	Brightness, Contrast, Saturation, Hue, Sharpness, Gamma, White balance, Backlight Contrast, Exposure
-----------------------	--

Cable length	Default 1m USB cable
--------------	----------------------

Module Size	38*38 mm
-------------	----------

WORKING CONDITION

Power Consumption	USB DC +5V Supply
-------------------	-------------------

Operating Temperature	-20° ~ +70°
-----------------------	-------------

Storage Temperature	-40° ~ +85°
---------------------	-------------

Humidity	80 ~85%
----------	---------

FORMAT	RESOLUTION	FRAME RATE	
		USB3.0	USB2.0
MJPEG	1920x1080 (1080P)		30fps
	1280X720 (720P)		30fps
	640X480 (VGA)		30fps
YUY2	1920x1080 (1080P)		5fps
	1280X720 (720P)		10fps
	640X480 (VGA)		30fps

PRODUCT DIMENSION

